

产品认证证书

证书编号: CQC16001150402

发证日期: 2023 年 09 月 01 日 有效期至: 2028 年 04 月 17 日

委托人名称 亚德诺投资有限公司

及注册地址 上海市黄浦区湖滨路 222 号 11 层 (实际楼层为 10 层) 1107 室

制造商名称 Analog Devices

及注册地址 804 Woburn StreetWilmingtonMA 美国

生产企业名称 Analog Devices Gen. Trias

及生产地址 Sandoval St. Gateway Business Park Javalera, General Trias Cavite, 菲律宾 4107

产品名称和系列、数字隔离器

规格、型号 见附件(仅适用于海拔5000米及以下地区安全使用)

产品标准和技术要求 GB 4943.1-2022

认证模式 产品型式试验+初次工厂检查+获证后监督

上述产品符合 CQC11-471543-2022 认证规则的要求,特发此证。 本证书为变更证书,证书首次颁发日期:2016年08月23日 证书有效期内本证书的有效性依据发证机构的定期监督获得保持。

可通过扫描下方二维码或登录国家认监委网站(www.cnca.gov.cn)查验证书信息





中国质量认证中心

中国・北京・南四环西路188号9区 100070

电话: +86 10 83886666



cac)产品认证证书

证书编号: CQC16001150402

第1页/共1页

本证书及附件应同时使用,信息查验说明见证书页

纸号:

ADUM4400ARWZ, ADUM4400BRWZ, ADUM4400CRWZ, ADUM4401ARWZ, ADUM4401BRWZ, ADUM4401CRWZ, ADUM4402ARWZ, ADUM4402BRWZ, ADUM4402CRWZ , ADW80035ARWZ

外部爬电距离:7.7mm,通过热循环测试,加强绝缘:最大工作电压:380V 有效值,537V 峰值,基本绝缘:最大工作电压:760V 有效值,1075V 峰值。

ADUM4400ARIZ, ADUM4400BRIZ, ADUM4400CRIZ, ADUM4401ARIZ, ADUM4401BRIZ, ADUM4401CRIZ, ADUM4402ARIZ, ADUM4402BRIZ, ADUM4402CRIZ

外部爬电距离:8.3mm,通过热循环测试,加强绝缘:最大工作电压: 410V 有效值,578V 峰值,基本绝缘:最大工作电压:820V 有效值,1159V 峰值。

(仅适用于海拔 5000 米及以下)





CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO.: CQC16001150402 Valid from: Sep.01,2023 Valid until:Apr.17,2028

NAME AND REGISTERED Analog Devices (China) Holdings Co., Ltd.

ADDRESS OF THE APPLICANT Room 1107, 11th floor (Actual 10th floor) , #222 Hubin Road, Huangpu District, Shanghai

NAME AND REGISTERED Analog Devices

ADDRESS OF THE 804 Woburn StreetWilmingtonMA, USA

MANUFACTURER

NAME AND LOCATION Analog Devices Gen. Trias

OF THE FACTORY Sandoval St. Gateway Business Park Javalera, General Trias Cavite, Philippines 4107

PRODUCT NAME, MODEL Digital Isolator

AND SPECIFICATION See Annex (Altitude up to 5000m)

THE STANDARDS AND GB 4943.1-2022

TECHNICAL REQUIREMENTS
FOR THE PRODUCTS

TYPE OF CERTIFICATION

Type Testing of Product + Initial Factory Inspection + Follow up Factory Inspection

SCHEMES

This is to certify that the above mentioned product(s) complies with the requirements of certification rules of CQC11-471543-2022.

Date of original issued: Aug.23,2016

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

The certificate information is available through the QR code below or CNCA's website: www.cnc




SIGNATURE



CHINA QUALITY CERTIFICATION CENTRE

Tel: +86 10 83886666



Section 9, No. 188, Nansihuan Xilu, Beijing 100070 P.R.China



CERTIFICATE OF PRODUCT CERTIFICATION

CERTIFICATE NO.: CQC16001150402

page1of1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

ADUM4400ARWZ, ADUM4400BRWZ, ADUM4400CRWZ, ADUM4401ARWZ, ADUM4401BRWZ, ADUM4401CRWZ, ADUM4402ARWZ, ADUM4402BRWZ, ADUM4402CRWZ, ADW80035ARWZ

外部爬电距离:7.7mm,通过热循环测试,加强绝缘:最大工作电压:380V 有效值,537V 峰值,基本绝缘:最大工作电压:760V 有效值,1075V 峰值。

ADUM4400ARIZ, ADUM4400BRIZ, ADUM4400CRIZ, ADUM4401ARIZ, ADUM4401BRIZ, ADUM4401CRIZ, ADUM4402ARIZ, ADUM4402CRIZ

外部爬电距离:8.3mm,通过热循环测试,加强绝缘:最大工作电压: 410V 有效值,578V 峰值,基本绝缘:最大工作电压:820V 有效值,1159V 峰值。

(仅适用于海拔 5000 米及以下)

